

1N5391 THRU 1N5399

TECHNICAL SPECIFICATIONS OF SILICON RECTIFIER

VOLTAGE: 50-1000V

CURRENT: 1.5A


FEATURES

- High reliability
- Low leakage
- Low forward voltage drop
- High current capability

MECHANICAL DATA

- **Case:** Molded plastic
- **Epoxy:** UL94V-0 rate flame retardant
- **Lead:** MIL-STD- 202E, Method 208 guaranteed
- **Polarity:** Color band denotes cathode end
- **Mounting position:** Any
- **Weight:** 0.38 grams

DO-15



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRONICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	SYMBOL	1N5391	1N5392	1N5393	1N5395	1N5397	1N5398	1N5399	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward rectified Current at T _L =75°C	I_o	1.5							A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	50							A
Maximum Instantaneous forward Voltage at 1.5A DC	V_F	1.1							V
Maximum DC Reverse Current @ T _A =25°C at Rated DC Blocking Voltage	I_R	5.0							μA
		500							
Maximum Full Load Reverse Current Average, Full Cycle .375"(9.5mm) lead length at T _L =75°C		30							
Typical Junction Capacitance (Note)	C_J	20							pF
Typical Thermal Resistance	R_{θJA}	50							°C/W

Notes: Measured at 1MHz and applied reverse voltage of 4.0 volts